

SOF[®] Seal Plus Gasket



Product Name:
SOF[®] Seal Plus

Flexible, continuous lengths of extruded, closed-cell polyethylene foam backer rod for use as a moisture and air infiltration barrier.

Features

- Easy to apply
- Non-gassing
- Non-exuding
- Chemically inert
- Virtually dust-free
- Meets all of the requirements of the 1990 Clean Air Act
- Is a "Domestic End Product" as defined in the Buy American Act, Title 41 USC 10

Physical Property Requirements		
Property	Value	ASTM Test Methods
Density lb/ft ³ (kg/m ³), avg.	1.3-2.3 (20-37)	D 1622
Outgassing (No. of Bubbles)	> 1	C 1253
Compression Recovery, %, min	> 90	D 5249
Compression Deflection psi (kgf/cm ²)	15 (1.05)	D 5249
Tensile Strength psi (kgf/cm ²), min	24 (1.69)	D 1623
Water Absorption (g/cc)	< .03	C 1016 - Procedure B

Description

Sof Seal Plus gasket is a "P" shaped profile intended for use as a seal for marriage walls in modular construction.
TEMPERATURE LIMITS: -45°F to +160°F.

Benefits

Sof Seal Plus gasket is economical, easy to install and resists snags and tears common with polyurethane foam products.

Applications

Used as a gasket in modular and mobile home construction and other applications requiring a barrier for moisture and air infiltration.

Storage

Store in a well ventilated area. Do not store products in direct sunlight. Keep away from heat sources and open flames.